



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

SECTION 1: Identification

1.1 Product identifier

Trade name **WELD-ON 717 ECO GRAY**
Product category/ies Eco Friendly Heavy Bodied PVC Solvent Cement

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses adhesive
PVC solvent cement

1.3 Details of the supplier of the safety data sheet

Weld-On
17109 S. Main
Gardena CA 90248-3127
United States

Telephone: 1-310-898-3300
e-mail: EHSInfo@ipscorp.com
Website: www.weldon.com

1.4 Emergency telephone number

Emergency information service 24 Hours - CHEMTEL: (800) 255-3924; International (813) 248-0585

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

| Hazard class | Category |
|---|----------|
| acute toxicity (oral) | 4 |
| acute toxicity (inhal.) | 4 |
| skin corrosion/irritation | 2 |
| serious eye damage/eye irritation | 2 |
| skin sensitization | 1 |
| specific target organ toxicity - single exposure (respiratory tract irritation) | 3 |
| specific target organ toxicity - single exposure (narcotic effects, drowsiness) | 3 |
| flammable liquid | 2 |

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS07



- Hazard statements

| | |
|-----------|--------------------------------------|
| H225 | Highly flammable liquid and vapor. |
| H302+H332 | Harmful if swallowed or if inhaled. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |

- Precautionary statements

| | |
|----------------|--|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P103 | Read label before use. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. No smoking. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/lighting equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P261 | Avoid breathing dust/fume/gas/mist/vapors/spray. |
| P270 | Do not eat, drink or smoke when using this product. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P272 | Contaminated work clothing must not be allowed out of the workplace. |
| P280 | Wear protective gloves/eye protection/face protection. |
| P301+P312 | If swallowed: Call a poison center/doctor if you feel unwell. |
| P302+P352 | If on skin: Wash with plenty of water. |
| P303+P361+P353 | If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+P340 | If inhaled: Remove person to fresh air and keep comfortable for breathing. |
| P305+P351+P338 | If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312 | Call a poison center/doctor if you feel unwell. |
| P321 | Specific treatment (see on this label). |
| P330 | Rinse mouth. |
| P362 | Take off contaminated clothing and wash before reuse. |
| P363 | Wash contaminated clothing before reuse. |
| P370+P378 | In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container to industrial combustion plant. |

- Hazardous ingredients for labelling proprietary additive, cyclohexanone, methyl ethyl ketone

2.3 Other hazards

Special danger of slipping by leaking/spilling product.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

Hazards not otherwise classified

Contains proprietary additive, proprietary additive. May produce an allergic reaction.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

| Name of substance | Identifier | Wt% | Classification acc. to GHS |
|----------------------|-----------------------|-----------|---|
| cyclohexanone | CAS No 108-94-1 | 25 - < 50 | Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Flam. Liq. 3 / H226 |
| methyl ethyl ketone | CAS No 78-93-3 | 25 - < 50 | Eye Irrit. 2 / H319 STOT SE 3 / H336 Flam. Liq. 2 / H225 |
| acetone | CAS No 67-64-1 | 10 - < 25 | Eye Irrit. 2 / H319 STOT SE 3 / H336 Flam. Liq. 2 / H225 |
| proprietary additive | CAS No proprietary | < 1 | Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Skin Sens. 1 / H317 |
| proprietary additive | CAS No proprietary | < 1 | Acute Tox. 4 / H302 Acute Tox. 3 / H311 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Skin Sens. 1 / H317 Muta. 2 / H341 STOT SE 1 / H370 STOT RE 1 / H372 |

For full text of abbreviations: see SECTION 16.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

Flash point

1.4 °F

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Occupational exposure limit values (Workplace Exposure Limits) | | | | | | | | | | | |
|--|------------------------|----------|------------|-----------|--------------------------|------------|---------------------------|-----------------|--------------------------------|----------|------------------|
| Country | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m ³] | STEL [ppm] | STEL [mg/m ³] | Ceiling-C [ppm] | Ceiling-C [mg/m ³] | Notation | Source |
| US | tin, organic compounds | | PEL (CA) | | 0.1 | | 0.2 | | | Sn | Cal/ OSHA PEL |
| US | tin, organic compounds | | REL | | 0.1 (10 h) | | | | | Sn | NIOSH REL |
| US | tin, organic compounds | | PEL | | 0.1 | | | | | Sn | 29 CFR 1910.1000 |
| US | tin, organic compounds | | TLV® | | 0.1 | | 0.2 | | | Sn, H | ACGIH® 2023 |
| US | cyclohexanone | 108-94-1 | PEL (CA) | 25 | 100 | | | | | | Cal/ OSHA PEL |
| US | cyclohexanone | 108-94-1 | REL | 25 (10 h) | 100 (10 h) | | | | | | NIOSH REL |
| US | cyclohexanone | 108-94-1 | PEL | 50 | 200 | | | | | | 29 CFR 1910.1000 |
| US | cyclohexanone | 108-94-1 | TLV® | 20 | | 50 | | | | H | ACGIH® 2023 |
| US | acetone | 67-64-1 | PEL (CA) | 500 | 1,200 | 750 | 1,780 | 3,000 | | | Cal/ OSHA PEL |



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

Occupational exposure limit values (Workplace Exposure Limits)

| Country | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m ³] | STEL [ppm] | STEL [mg/m ³] | Ceiling-C [ppm] | Ceiling-C [mg/m ³] | Notation | Source |
|---------|--|-----------|------------|------------|--------------------------|------------|---------------------------|-----------------|--------------------------------|----------|------------------|
| US | acetone | 67-64-1 | REL | 250 (10 h) | 590 (10 h) | | | | | | NIOSH REL |
| US | acetone | 67-64-1 | TLV® | 250 | | 500 | | | | | ACGIH® 2023 |
| US | acetone | 67-64-1 | PEL | 1,000 | 2,400 | | | | | | 29 CFR 1910.1000 |
| US | silica, amorphous | 7631-86-9 | REL | | 6 (10 h) | | | | | | NIOSH REL |
| US | 2-butanone | 78-93-3 | REL | 200 (10 h) | 590 (10 h) | 300 | 885 | | | | NIOSH REL |
| US | 2-butanone (methyl ethyl ketone) | 78-93-3 | PEL | 200 | 590 | | | | | | 29 CFR 1910.1000 |
| US | methyl ethyl ketone | 78-93-3 | TLV® | 200 | | 300 | | | | | ACGIH® 2023 |
| US | methyl ethyl ketone (MEK) (2-butanone) (ethyl methyl ketone) | 78-93-3 | PEL (CA) | 200 | 590 | 300 | 885 | | | | Ca/ OSHA PEL |
| US | polyvinyl chloride | 9002-86-2 | TLV® | | 1 | | | | | r | ACGIH® 2023 |

Notation

Ceiling-C

H

r

Sn

STEL

TWA

ceiling value is a limit value above which exposure should not occur absorbed through the skin

respirable fraction

calculated as Sn (tin)

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values

| Country | Name of agent | Parameter | Notation | Identifier | Value | Source |
|---------|---------------------|---------------------|----------|------------|---------|-------------|
| US | cyclohexanone | 1,2-cyclohexanediol | hydr | BEI® | 80 mg/l | ACGIH® 2023 |
| US | cyclohexanone | cyclohexanol | hydr | BEI® | 8 mg/l | ACGIH® 2023 |
| US | tetrahydrofuran | tetrahydrofuran | | BEI® | 2 mg/l | ACGIH® 2023 |
| US | acetone | acetone | | BEI® | 25 mg/l | ACGIH® 2023 |
| US | methyl ethyl ketone | methyl ethyl ketone | | BEI® | 2 mg/l | ACGIH® 2023 |

Notation

hydr

hydrolysis



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

Relevant DNELs of components of the mixture

| Name of substance | CAS No | Endpoint | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
|----------------------|-------------|----------|-------------------------|------------------------------------|-------------------|----------------------------|
| cyclohexanone | 108-94-1 | DNEL | 10 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| cyclohexanone | 108-94-1 | DNEL | 20 mg/m ³ | human, inhalatory | worker (industry) | acute - systemic effects |
| cyclohexanone | 108-94-1 | DNEL | 10 mg/m ³ | human, inhalatory | worker (industry) | chronic - local effects |
| cyclohexanone | 108-94-1 | DNEL | 20 mg/m ³ | human, inhalatory | worker (industry) | acute - local effects |
| cyclohexanone | 108-94-1 | DNEL | 4 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| cyclohexanone | 108-94-1 | DNEL | 4 mg/kg bw/day | human, dermal | worker (industry) | acute - systemic effects |
| methyl ethyl ketone | 78-93-3 | DNEL | 600 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| methyl ethyl ketone | 78-93-3 | DNEL | 1,161 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| acetone | 67-64-1 | DNEL | 1,210 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| acetone | 67-64-1 | DNEL | 2,420 mg/m ³ | human, inhalatory | worker (industry) | acute - local effects |
| acetone | 67-64-1 | DNEL | 186 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| proprietary additive | proprietary | DNEL | 4.7 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| proprietary additive | proprietary | DNEL | 6.66 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| proprietary additive | proprietary | DNEL | 0.3 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| proprietary additive | proprietary | DNEL | 1.58 mg/m ³ | human, inhalatory | worker (industry) | acute - systemic effects |
| proprietary additive | proprietary | DNEL | 4.25 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| proprietary additive | proprietary | DNEL | 8.5 mg/kg bw/day | human, dermal | worker (industry) | acute - systemic effects |

Relevant PNECs of components of the mixture

| Name of substance | CAS No | Endpoint | Threshold level | Organism | Environmental compartment | Exposure time |
|-------------------|----------|----------|-----------------|-------------------|---------------------------|------------------------------|
| cyclohexanone | 108-94-1 | PNEC | 0.356 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| cyclohexanone | 108-94-1 | PNEC | 0.036 mg/l | aquatic organisms | marine water | short-term (single instance) |



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

| Relevant PNECs of components of the mixture | | | | | | |
|---|-------------|----------|-----------------|-----------------------|------------------------------|------------------------------|
| Name of substance | CAS No | Endpoint | Threshold level | Organism | Environmental compartment | Exposure time |
| cyclohexanone | 108-94-1 | PNEC | 10 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| cyclohexanone | 108-94-1 | PNEC | 2.69 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| cyclohexanone | 108-94-1 | PNEC | 0.269 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| cyclohexanone | 108-94-1 | PNEC | 0.328 mg/kg | terrestrial organisms | soil | short-term (single instance) |
| methyl ethyl ketone | 78-93-3 | PNEC | 55.8 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| methyl ethyl ketone | 78-93-3 | PNEC | 55.8 mg/l | aquatic organisms | marine water | short-term (single instance) |
| methyl ethyl ketone | 78-93-3 | PNEC | 709 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| methyl ethyl ketone | 78-93-3 | PNEC | 284.7 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| methyl ethyl ketone | 78-93-3 | PNEC | 284.7 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| methyl ethyl ketone | 78-93-3 | PNEC | 22.5 mg/kg | terrestrial organisms | soil | short-term (single instance) |
| acetone | 67-64-1 | PNEC | 10.6 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| acetone | 67-64-1 | PNEC | 1.06 mg/l | aquatic organisms | marine water | short-term (single instance) |
| acetone | 67-64-1 | PNEC | 100 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| acetone | 67-64-1 | PNEC | 30.4 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| acetone | 67-64-1 | PNEC | 3.04 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| acetone | 67-64-1 | PNEC | 29.5 mg/kg | terrestrial organisms | soil | short-term (single instance) |
| proprietary additive | proprietary | PNEC | 0.024 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| proprietary additive | proprietary | PNEC | 0.002 mg/l | aquatic organisms | marine water | short-term (single instance) |
| proprietary additive | proprietary | PNEC | 100 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| proprietary additive | proprietary | PNEC | 0.084 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

| Relevant PNECs of components of the mixture | | | | | | |
|---|-------------|----------|-----------------|-----------------------|------------------------------|------------------------------|
| Name of substance | CAS No | Endpoint | Threshold level | Organism | Environmental compartment | Exposure time |
| proprietary additive | proprietary | PNEC | 0.008 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| proprietary additive | proprietary | PNEC | 0.003 mg/kg | terrestrial organisms | soil | short-term (single instance) |
| proprietary additive | proprietary | PNEC | 0.007 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| proprietary additive | proprietary | PNEC | 0.001 mg/l | aquatic organisms | marine water | short-term (single instance) |
| proprietary additive | proprietary | PNEC | 10 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| proprietary additive | proprietary | PNEC | 0.032 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| proprietary additive | proprietary | PNEC | 0.003 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| proprietary additive | proprietary | PNEC | 0.025 mg/kg | terrestrial organisms | soil | short-term (single instance) |

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

| | |
|----------------|-----------------------|
| Physical state | liquid (viscous) |
| Color | gray |
| Particle | not relevant (liquid) |
| Odor | characteristic |

Other safety parameters

| | |
|---|-----------------------------------|
| pH (value) | not determined |
| Melting point/freezing point | not determined |
| Initial boiling point and boiling range | 56.05 °C |
| Flash point | -17 °C |
| Flash point | 1.4 °F |
| Evaporation rate | not determined |
| Flammability (solid, gas) | not relevant, (fluid) |
| Vapor pressure | 240 hPa at 20 °C |
| Density | 0.934 g/cm ³ at 73 °F |
| Vapor density | this information is not available |
| Solubility(ies) | not determined |

Partition coefficient

| | |
|-----------------------------|--|
| - n-octanol/water (log KOW) | this information is not available |
| Auto-ignition temperature | 420 °C (auto-ignition temperature (liquids and gases)) |

Viscosity

| | |
|---------------------|---------------------------|
| - Dynamic viscosity | 1,500 – 2,400 cP at 73 °F |
|---------------------|---------------------------|



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

| | |
|----------------------|------|
| Explosive properties | none |
| Oxidizing properties | none |

9.2 Other information

| | |
|--|---|
| VOC content | When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: ≤ 425 g/L. |
| Temperature class (USA, acc. to NEC 500) | T2 (maximum permissible surface temperature on the equipment: 300°C) |

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if swallowed. Harmful if inhaled.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

GHS of the United Nations, annex 4: May be harmful in contact with skin.

- Acute toxicity estimate (ATE)

Oral 1,515 mg/kg
Inhalation: vapor 18.62 mg/l/4h

Acute toxicity estimate (ATE) of components of the mixture

| Name of substance | CAS No | Exposure route | ATE |
|----------------------|-------------|-----------------------|---------------|
| cyclohexanone | 108-94-1 | oral | 500 mg/kg |
| cyclohexanone | 108-94-1 | dermal | 1,100 mg/kg |
| cyclohexanone | 108-94-1 | inhalation: vapor | >6.2 mg/l/4h |
| proprietary additive | proprietary | oral | 1,163 mg/kg |
| proprietary additive | proprietary | inhalation: vapor | 11 mg/l/4h |
| proprietary additive | proprietary | oral | 396 mg/kg |
| proprietary additive | proprietary | dermal | 777 mg/kg |
| proprietary additive | proprietary | inhalation: vapor | 3 mg/l/4h |
| proprietary additive | proprietary | inhalation: dust/mist | 0.941 mg/l/4h |

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

| Name of substance | CAS No | Classification | Number |
|-------------------|----------|----------------|--------|
| cyclohexanone | 108-94-1 | 3 | |

Legend

3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

SECTION 14: Transport information

14.1 UN number

| | |
|-----------|---------|
| DOT | UN 1133 |
| IMDG-Code | UN 1133 |
| ICAO-TI | UN 1133 |

14.2 UN proper shipping name

| | |
|-----------|-----------|
| DOT | Adhesives |
| IMDG-Code | ADHESIVES |
| ICAO-TI | Adhesives |

14.3 Transport hazard class(es)

| | |
|-----------|---|
| DOT | 3 |
| IMDG-Code | 3 |
| ICAO-TI | 3 |

14.4 Packing group

| | |
|-----------|----|
| DOT | II |
| IMDG-Code | II |
| ICAO-TI | II |

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

| | |
|--|---|
| Particulars in the shipper's declaration | UN1133, Adhesives, 3, II |
| Reportable quantity (RQ) | 15,152 lbs (6,879 kg) (cyclohexanone) (methyl ethyl ketone) |
| Danger label(s) | 3 |



| | |
|-------------------------|-----------------------------|
| Special provisions (SP) | 149, B52, IB2, T4, TP1, TP8 |
| ERG No | 128 |

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant -
Danger label(s) 3



Special provisions (SP) -
Excepted quantities (EQ) E2
Limited quantities (LQ) 5 L
EmS F-E, S-D
Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 3



Special provisions (SP) A3
Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed as ACTIVE

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

| Name of substance | CAS No | Remarks | Statutory code | Final RQ pounds (Kg) |
|---------------------|----------|---------|----------------|----------------------|
| methyl ethyl ketone | 78-93-3 | | 4 | 5000 (2270) |
| cyclohexanone | 108-94-1 | | 4 | 5000 (2270) |
| acetone | 67-64-1 | | 4 | 5000 (2270) |

Legend

4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

| Name of substance | CAS No | Functionality | Authoritative Lists |
|----------------------|-----------|---------------|---|
| methyl ethyl ketone | 78-93-3 | | ATSDR Neurotoxicants CA TACs OEHHA RELs |
| acetone | 67-64-1 | | ATSDR Neurotoxicants |
| proprietary additive | 7440-31-5 | | OSPAR Priority Action Part A |

- Toxic or Hazardous Substance List (MA-TURA)

| Name of substance | CAS No | DEP CODE | PBT / HHS / LHS | PBT / HHS Threshold | De Minimis Concentration Threshold |
|---------------------|----------|----------|-----------------|---------------------|------------------------------------|
| methyl ethyl ketone | 78-93-3 | | | | 1.0 % |
| cyclohexanone | 108-94-1 | | | | 1.0 % |
| acetone | 67-64-1 | | | | 1.0 % |

- Hazardous Substances List (MN-ERTK)

| Name of substance | CAS No | References | Remarks |
|----------------------|----------|------------|---------|
| methyl ethyl ketone | 78-93-3 | A, N, O | |
| cyclohexanone | 108-94-1 | A, N, O | skin |
| acetone | 67-64-1 | A, N, O | |
| proprietary additive | | N, * | |

Legend

- * Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).
- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division
- skin If a potential for absorption from skin contact merits special consideration, the word "skin" follows the substance name.

- Hazardous Substance List (NJ-RTK)

| Name of substance | CAS No | Remarks | Classifications |
|---------------------|----------|---------|-----------------|
| methyl ethyl ketone | 78-93-3 | | F3 |
| cyclohexanone | 108-94-1 | | F2 |
| acetone | 67-64-1 | | F3 |

Legend

- F2 Flammable - Second Degree



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

Legend

F3 Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

| Name acc. to inventory | CAS No | Classification |
|------------------------|----------|----------------|
| 2-BUTANONE | 78-93-3 | E |
| CYCLOHEXANONE | 108-94-1 | E |
| 2-PROPANONE | 67-64-1 | E |

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

| Name of substance | CAS No | References |
|----------------------|-----------|------------|
| methyl ethyl ketone | 78-93-3 | T, F |
| cyclohexanone | 108-94-1 | T, F |
| acetone | 67-64-1 | T, F |
| proprietary additive | 7440-31-5 | T |

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

| Category | Rating | Description |
|---------------------|--------|--|
| Chronic | * | chronic (long-term) health effects may result from repeated overexposure |
| Health | 2 | temporary or minor injury may occur |
| Flammability | 3 | material that can be ignited under almost all ambient temperature conditions |
| Physical hazard | 0 | material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive |
| Personal protection | - | |

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

| Category | Degree of hazard | Description |
|----------------|------------------|--|
| Flammability | 3 | material that can be ignited under almost all ambient temperature conditions |
| Health | 2 | material that, under emergency conditions, can cause temporary incapacitation or residual injury |
| Instability | 0 | material that is normally stable, even under fire conditions |
| Special hazard | | |

National inventories

| Country | Inventory | Status |
|---------|------------|-------------------------------------|
| AU | AIIC | all ingredients are listed |
| CA | DSL | all ingredients are listed |
| CN | IECSC | all ingredients are listed |
| EU | ECSI | not all ingredients are listed |
| JP | CSCL-ENCS | not all ingredients are listed |
| JP | ISHA-ENCS | not all ingredients are listed |
| KR | KECI | all ingredients are listed |
| MX | INSQ | not all ingredients are listed |
| NZ | NZIoC | all ingredients are listed |
| PH | PICCS | all ingredients are listed |
| TW | TCSI | all ingredients are listed |
| US | TSCA | all ingredients are listed (ACTIVE) |
| EU | REACH Reg. | not all ingredients are listed |
| TR | CICR | not all ingredients are listed |

Legend

| | |
|------------|---|
| AIIC | Australian Inventory of Industrial Chemicals |
| CICR | Chemical Inventory and Control Regulation |
| CSCL-ENCS | List of Existing and New Chemical Substances (CSCL-ENCS) |
| DSL | Domestic Substances List (DSL) |
| ECSI | EC Substance Inventory (EINECS, ELINCS, NLP) |
| IECSC | Inventory of Existing Chemical Substances Produced or Imported in China |
| INSQ | National Inventory of Chemical Substances |
| ISHA-ENCS | Inventory of Existing and New Chemical Substances (ISHA-ENCS) |
| KECI | Korea Existing Chemicals Inventory |
| NZIoC | New Zealand Inventory of Chemicals |
| PICCS | Philippine Inventory of Chemicals and Chemical Substances (PICCS) |
| REACH Reg. | REACH registered substances |
| TCSI | Taiwan Chemical Substance Inventory |
| TSCA | Toxic Substance Control Act |

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

| Section | Former entry (text/value) | Actual entry (text/value) | Safety-relevant |
|---------|---|---|-----------------|
| 2.2 | | - Precautionary statements: change in the listing (table) | yes |
| 2.3 | | Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$. | yes |
| 2.3 | | Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$. | yes |
| 8.1 | | Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table) | yes |
| 8.1 | | Biological limit values: change in the listing (table) | yes |
| 9.2 | VOC content: When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: ≤ 400 g/L. | VOC content: When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: ≤ 425 g/L. | yes |
| 12.5 | Results of PBT and vPvB assessment: Data are not available. | Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$. | yes |
| 12.6 | Endocrine disrupting properties: Information on this property is not available. | Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$. | yes |
| 15.1 | Toxic Substance Control Act (TSCA): all ingredients are listed | Toxic Substance Control Act (TSCA): all ingredients are listed as ACTIVE | yes |
| 15.1 | | List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4): change in the listing (table) | yes |
| 15.1 | | Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table) | yes |
| 15.1 | | Hazardous Substance List (RI-RTK): change in the listing (table) | yes |
| 15.1 | | National inventories: change in the listing (table) | yes |

Abbreviations and acronyms



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

| Abbr. | Descriptions of used abbreviations |
|------------------|--|
| 29 CFR 1910.1000 | 29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits) |
| 49 CFR US DOT | 49 CFR U.S. Department of Transportation |
| ACGIH® | American Conference of Governmental Industrial Hygienists |
| ACGIH® 2023 | From ACGIH®, 2023 TLVs® and BEIs® Book. Copyright 2023. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement |
| Acute Tox. | Acute toxicity |
| ATE | Acute Toxicity Estimate |
| Cal/OSHA PEL | California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs) |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| Ceiling-C | Ceiling value |
| DEP CODE | Department of Environmental Protection Code |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| DNEL | Derived No-Effect Level |
| DOT | Department of Transportation (USA) |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| ELINCS | European List of Notified Chemical Substances |
| EmS | Emergency Schedule |
| ERG No | Emergency Response Guidebook - Number |
| Eye Dam. | Seriously damaging to the eye |
| Eye Irrit. | Irritant to the eye |
| Flam. Liq. | Flammable liquid |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |
| HHS | Higher hazard substance |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| ICAO-TI | Technical instructions for the safe transport of dangerous goods by air |
| IMDG | International Maritime Dangerous Goods Code |
| IMDG-Code | International Maritime Dangerous Goods Code |
| LHS | Lower hazard substance |
| Muta. | Germ cell mutagenicity |



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

| Abbr. | Descriptions of used abbreviations |
|----------------|---|
| NFPA® | National Fire Protection Association (United States) |
| NIOSH REL | National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) |
| NLP | No-Longer Polymer |
| NPCA-HMIS® III | National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition |
| OSHA | Occupational Safety and Health Administration (United States) |
| PBT | Persistent, Bioaccumulative and Toxic |
| PEL | Permissible exposure limit |
| PNEC | Predicted No-Effect Concentration |
| ppm | Parts per million |
| RTECS | Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information) |
| Skin Corr. | Corrosive to skin |
| Skin Irrit. | Irritant to skin |
| Skin Sens. | Skin sensitization |
| STEL | Short-term exposure limit |
| STOT RE | Specific target organ toxicity - repeated exposure |
| STOT SE | Specific target organ toxicity - single exposure |
| TLV® | Threshold Limit Values |
| TWA | Time-weighted average |
| VOC | Volatile Organic Compounds |
| vPvB | Very Persistent and very Bioaccumulative |

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|------|------------------------------------|
| H225 | Highly flammable liquid and vapor. |
| H226 | Flammable liquid and vapor. |
| H302 | Harmful if swallowed. |



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WELD-ON 717 ECO GRAY

Version number: 2.0
Replaces version of: 2022-05-10 (1)

Revision: 2023-04-12

| Code | Text |
|------|---|
| H311 | Toxic in contact with skin. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H341 | Suspected of causing genetic defects. |
| H370 | Causes damage to organs. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.