

ECOTM SERIES

The strength you trust, now with ultra low voc.

- Superior joint strength
- Fast setting
- 30% lower solvent emissions
- Less odorous fumes
- Improved working environment



Breathe easier

www.weldon.com



ECO™ SERIES

	Max Pipe Size	Set Time	Available Color	Performance Specification
	4" (110 mm) Not for Sch. 80	Fast		 PW-G/DWV/SW U.P. CODE ASTM D2564 NSF/ANSI 14 & 61
	6" (160 mm) 4" (110 mm) Sch. 80	Fast	 	 C US PW-G/DWV/SW U.P. CODE (GRAY ONLY)  PW-G/DWV/SW U.P. CODE ASTM D2564 NSF/ANSI 14 & 61 CSA B137.3 CSA B181.2
	6" (160 mm) 4" (110 mm) Sch. 80	Fast		 PW-G/DWV/SW U.P. CODE ASTM D2564 NSF/ANSI 14 & 61
	12" (315 mm)	Medium		 C US PW-G/DWV/SW U.P. CODE ASTM D2564 NSF/ANSI 14 & 61
	12" (315 mm)	Medium	 	 C US PW-G/DWV/SW U.P. CODE (GRAY ONLY)  PW-G/DWV/SW U.P. CODE ASTM D2564 NSF/ANSI 14 & 61 CSA B137.3 CSA B181.2
	—	—	 	 C US U.P. CODE (PURPLE ONLY) ASTM F656 NSF/ANSI 14 & 61