



## C-65™ ECO Max™ Cleaner

For removal of oil and grease from the surfaces of PVC and CPVC pipe and fittings. Recommended for use before priming of pipe and fittings.

### PRODUCT SPECIFICATIONS

Pipe type	All PVC, CPVC, ABS, & Styrene
Cleaner Use	Remove oil and grease from the surfaces of PVC, CPVC, ABS and STYRENE pipe and fittings.
Color	Clear
Brookfield Viscosity	Water-thin
Specific Gravity	0.798 ± 0.04
Shelf Life	3 Years

### SPECIAL PRECAUTION

Weld-On solvent products must never be used in plastic piping system using or being tested by compressed air or gases; including air-over-water booster. Do not use in conjunction with flue gas ventilation systems.

Do not use a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system – this solution will be nonvolatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

This product is intended for use by skilled individuals at their own risk. Installers should verify for themselves that they can make satisfactory joints under varying conditions. Detailed directions on making solvent cemented joints are printed on the container label. It is highly recommended that the installer review the instructions supplied by the pipe and fitting manufacturer.

**Refer to the current Safety Data Sheet for additional safety precautions, first-aid, storage, handling, transportation and disposal information.**

**Refer to website for complete Terms and Conditions.**