



PVC & ABS Cleaner

Weld-On® PVC & ABS Cleaner products are universal cleaning agent and can be used in combination with specific Weld-On® solvent cements.

- Cleaning of the materials to be jointed in order to create an optimal final bond
- Cleaning of equipment
- Remove of adhesive residues

PRODUCT SPECIFICATIONS

Base	Organic flammable solvent
Viscosity	10 mPa.s
Density	0,80 g/ml
Flashpoint	<0°C
Application temperature (min)	+5°C
Storage and transport temperature	<35°C
Shelf life	18 months in unopened packaging

SPECIAL PRECAUTION

Weld-On solvent cements must never be used in plastic piping system using or being tested by compressed air or gases; including air-over-water booster. Do not use in conjunction with flue gas ventilation systems.

Do not use a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system – this solution will be nonvolatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

This product is intended for use by skilled individuals at their own risk. Installers should verify for themselves that they can make satisfactory joints under varying conditions. Detailed directions on making solvent cemented joints are printed on the container label. It is highly recommended that the installer review the instructions supplied by the pipe and fitting manufacturer.

Refer to the current Safety Data Sheet for additional safety precautions, first-aid, storage, handling, transportation and disposal information.

Refer to website for complete Terms and Conditions.